

DUROSTICK THINNER 201 Thinner for epoxy systems

PROPERTIES

Special purpose thinner for epoxy systems, consisting of glycols and a mixture of aromatic hydrocarbons.

Clean them from oils and rust residues. Use it also to clean the epoxy system application tools and equipment thoroughly.

APPLICATIONS

DUROSTICK THINNER 201 is used primarily for thinning the two component epoxy paint DUROEPOXY, the two component epoxy primer DUROEPOXY PRIMER and the ALUMINUM & GALVANISED PRIMER of DUROSTICK. Use it to clean metal structures and constructs, after their sanding.

USE

Add DUROSTICK THINNER 201 at a ratio of 1-5% in DUROEPOXY PRIMER and 5-10% in DUROEPOXY of DUROSTICK, always following the recommended dilution rate posted on the application and use instructions on each product's packaging.



TECHNICAL SPECIFICATIONS

Form - Color	Liquid - Transparent
Density	0.90 ± 0.05 kg/lit
Application temperature	From + 5°C to +35°C

CONSUMPTION

1-5% in DUROEPOXY PRIMER and 5-10% in DUROEPOXY

STORAGE

Store in places protected from high temperatures and direct exposure to sunligh, for at least 12 months from production date.

SAFETY DIRECTIONS

The product is classified as highly flammable and harmful. It is recommended to keep away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

PACKAGING

Carton box with 15 pcs of 1lt each one