

## Crystal clear wood & paper glue



### PROPERTIES

PVA based, viscous glue, suitable for strong adhesions of wood and paper materials. Apply it easily using its container bottle with the controlled flow nozzle. It becomes clear when dries and it offers easy and quick bonding. Ideal for repairs, handicrafts, and various hobby constructions whether at school, at home, and/or at the office. Odorless, non-flammable, non-toxic, friendly to user and the environment.

### APPLICATIONS

DUROSTICK HOBBY strongly bonds wood, particle board, MDF, plywood, ceramics, paper, carton, modeling paper, wallpaper, polystyrene, cork, with each other and to other materials and/or surfaces.

### USE

1. Surface preparation  
Clean all bonding surfaces from dust and loose materials.
2. Application

Apply the undiluted glue uniformly on clean and dry surfaces. Allow for 5-10 minutes to pass and bond the parts together by pressing them firmly. Use clamps for 2-4 hours for better adhesion of all wood surfaces. The glue obtains its final strength 24 hours after the application without staining the wood surfaces. Clean any possible glue residues with a wet cloth or a sponge.

### LIMITATION OF USE

It is not recommended to use the adhesive when the temperature is below +8°C. While the adhesive is still fresh, the temperature should not drop below + 4°C.

### CLEANING

Remove any residue that might accumulate using a wet cloth or a sponge while the adhesive is still fresh. After the application, clean all tools and any residues with water and clean hands with warm water.

### CONSUMPTION

Depending on the absorbency and the nature of the surface.

# HOBBY



## Crystal clear wood & paper glue

### STORAGE

Store in the factory sealed packaging, in places protected from frost and heat, for at least 18 months from production date.

### SAFETY DIRECTIONS

The product needs no hazard labeling based on current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

### PACKAGING

Carton box with 20 bottles of 110gr each one

### TECHNICAL SPECIFICATIONS (Measurement conditions 23°C and 50% R.H.)

<b>Composition</b>	Viscous PVA
<b>Color</b>	White, becomes transparent when dry
<b>Density</b>	1.07±0.06kg/lit
<b>Solids by weight</b>	45% w/w
<b>Application temperature</b>	From +8°C to +35°C
<b>Adhesion strength</b>	3.50 N/mm <sup>2</sup> , after 48 hours (measurements on soft woods)

**Non-flammable, odorless, friendly to human and the environment**

### DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS  
 ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612  
 THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 10, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367  
 Email: [info@durostick.com](mailto:info@durostick.com)

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.