

## 6.2 Styles

# DECOFIN AQUA Acrylic waterborne matte finish varnish for styling vertical surfaces



### TECHNICAL SPECIFICATIONS

Form - Color	Liquid - White, becomes transparent when dry
Resin	Acrylic
Density	1.00 ± 0.05 kg/lit
Solids by weight	30 - 32 % w/w
Solids by volume	29 - 31 % w/v
pH	8.00 ± 0.5
Gloss	Matte
Application temperature	From +5°C to +35°C
Dilution	The product is ready to use. Do not dilute.
Drying time	Approximately one hour (touch dry), depending on the ambient conditions (humidity, temperature)
Recoating time	After 4 hours
Friendly to human and the environment	

#### V.O.C. (Volatile Organic Compounds):

Limit value of maximum V.O.C. content per EC (Directive 2004/42/EC) for the particular product (Class A/i: 'One-pack performance coatings' Type WB): 140 gr/lit (2010). Ready to use product contains maximum 75 gr/lit V.O.C.

### CLEANING

Clean all tools with water immediately after use, and if needed with soap or detergent solution.

### CONSUMPTION

1lt/12-13m<sup>2</sup> per coat, depending on the surface absorbency.

### STORAGE

Store in the factory sealed packages indoors, in places protected from frost, for at least 18 months from production date.

### SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

### NOTE

In places with high humidity, we recommend using the acrylic, solvent based varnish with matte finish, VISTA.

### PACKAGING

Carton box with 12 pcs of 750ml each one

### PROPERTIES

Acrylic, waterborne clear varnish of matte finish, suitable for use indoors.

It decorates and protects vertical surfaces styled with pressed cement screeds, decorative pastes, such as MATIZ Stucco Decorativo of DURO-STICK, or even styled with paints and colors. It highlights decorated surfaces while it remains clear. It gives surfaces depth without affecting their colors and uniqueness.

It protects surfaces from everyday use and allows for their cleaning with mild household detergents. It spreads evenly without leaving brush marks; it dries quickly and applies with exceptional ease, just like ordinary waterborne varnishes.

An odorless product that does not yellow over time nor does it peel off. Water soluble product that is friendly to human and the environment.

### APPLICATIONS

DECOFIN AQUA, waterborne, matte finish varnish protects indoor vertical surfaces decorated with paint, pressed cement screeds, DS-250, DS-252 FLEX, or DS-256 FLEX VELVET and, of course, decorative styling pastes (pic. 2) such as DS-258 DECO MICRO FLEX (pic. 1). It 'hugs' artistic creations with a clear, durable film while it ensures the durability and longevity of their

unique image for many years to come.

### USE

**1. Surface preparation:** Apply DECOFIN AQUA on sound, clean, and dust free surfaces.

All decorated surfaces have to be completely dry before applying the varnish. It is recommended that its application should be made no earlier than two days after the decorative style completion. In low temperature and high humidity conditions, the waiting period before the varnish application has to be made no earlier than four days after the decorative style completion.

The same time limitations apply when working with particularly thick decorative styling coats (e.g. surfaces decorated with pressed cement screeds, stucco, etc).

**2. Application:** DECOFIN AQUA is ready to use and it does not require any dilution. Mix the product very well and apply it in one to two coats using either roller and/or brush.

Touch dry in about one hour.

When applying a second coat, it is recommended to apply it no earlier than four hours after the first coat was completed.

All referred times depend on ambient conditions (temperature - humidity).



pic. 1



pic. 2