

6.6 Wood protection - stone varnishes & decorative coatings

VISTA SHINE Decorative waterborne varnish



TECHNICAL SPECIFICATIONS

Form - Color	Liquid - White, becomes transparent when dry
Resin	Acrylic polyurethane dispersions
Density	1.00±0.05 kg/lit
Solids by weight	25-28% w/w
Application temperature	From +5°C to +35°C
Solids by volume	23-26% w/v
pH	8.0±0.5
Gloss	Gloss
Dilution	The product is ready to use. Do not dilute
Drying time	Approximately 1 hour (touch dry), depending on the ambient conditions (temperature, humidity)
Recoating time	After 4 hours
Friendly to human and the environment	

V.O.C. (Volatile Organic Compounds): Limit value of maximum content of V.O.C. per EC (Directive 2004/42 / EC) for this product (category A1b: 'Interior glossy walls and ceilings', type WB): 100 g/lit (2010). The ready to use product contains maximum 95 gr/lit V.O.C.

CONSUMPTION

1lt/9-11m², depending on the absorbency of the surface.

STORAGE

Store in the factory sealed containers, for up to 18 months from production date.

SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep the product away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

LIMITATION OF USE

In spaces with high concentrations of humidity, its use is not recommended.

PACKAGING

Carton box with 12 pcs of 750ml each one

Carton box with 4 pcs of 2.5lt each one

PROPERTIES

Acrylic decorative waterborne varnish for vertical interior surfaces. It is ideal for converting ordinary walls or ceilings, decorative pressed cement screed surfaces, and wood or metal surfaces into impressive murals that magically radiate bright light.

Its special formula is based on a blend of acrylic and polyurethane resins that ensure longevity and resistance to frequent surface cleaning with mild detergents.

It applies uniformly without brush marks or paint lapping. It is quick drying and does not yellow.

The exceptional luster of VISTA SHINE highlights the radiant metallic specs in its composition, resulting in a wondrous reflection of light, regardless of its source.

It amazes with bright and everlasting surfaces of high decorative value. Those surfaces can be created with particular ease and provide impressive results with special styles.

The colorful highlights resemble forgotten flickering stars hiding in distant galaxies or tiny diamonds dancing playfully with the light passing through them from every direction. Waterborne, odorless product, that is Friendly to human and the environment.

APPLICATIONS

VISTA SHINE decorates and protects walls and ceilings already painted with emulsion or acrylic paints.

It also protects surfaces lined with decorative pressed cement screeds, DUROSTICK DS-250, DS-252 FLEX, DS-256 FLEX VELVET as well as wood surfaces such as doors and closets, painted with enamel paints. Apply it in one or several coats, depending on the intensity of the effect

desired from the surface.

It can be combined with modern or classic furniture.

Apply one coat for a discreet effect of the metallic specs; apply a second for more intensive effect and so on.

Thoroughly mix the product so that specks are distributed evenly throughout the varnish.

Use a short nap roller or a flat brush and apply just like any other varnish products.

Stir occasionally to maintain the even distribution of the specs.

If need be, VISTA SHINE can be re-coated with emulsion, acrylic and other waterborne coatings without requiring any particular preparation.

USE

1. Surface preparation

Surfaces must be clean, dry and free from dust. Already painted surfaces have to be stable and non faded.

2. Application

VISTA SHINE is a ready to use product. Do not dilute it.

Stir well before use, to homogenize the brilliant specks in the mass of the product.

Stir regularly during application to uniformly distribute the specks on the surface also.

Apply it using a roller or a brush, in one or multiple coats, depending on the desired intensity of the effect on the surface.

Surfaces coated with VISTA SHINE can be re-coated, if desired or needed, using high quality emulsion or acrylic coatings, without any particular preparation.

CLEANING

Clean all tools with water and if necessary with soap or detergent solution, immediately after use.

